






Net Cleaning System Specifications



High Pressure Washers*:	D-Drive K-300-240-SD-JD	D-Drive K-240-280-SD-JD	D-Drive K-136-280-SD-JD	D-Drive K-25065-1	D-Drive K-25065-2	D-Drive K-18050-M-5	F-Drive K-28-280-S-D-VA	D-Drive K-28-280-S-D-HZ-22	H-Drive K-28-280-SH	H-Drive K-30-200-SH
Engine:	John Deere Tier 3	John Deere Tier 3	John Deere Tier 3	Catepillar/Deutz**	Catepillar/Deutz**	Catepillar/Deutz**	Vanguard V-Twin	HATZ 2G40	Fitted to workboat	Fitted to workboat
Max hp:	202hp	202hp	156hp	310kw/400hp	315kw/400hp	150kw/200hp	23hp	22hp		
Pump type:	Prattisoli	Prattisoli	Prattisoli	Kamat	Kamat	Kamat				
Size:	300x135x180cm	300x135x180cm	300x135x180cm	304x243x280cm	-	360x240x280cm	120x60x75cm	120x80x80cm	60x35x25cm	60x35x25cm
Weight:	approx. 3000kg	approx. 2900kg	approx. 2750kg	approx. 7500kg	-	approx. 5000kg	80kg	180kg	40kg	40kg
Fuel:	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Gasoline	Diesel	Hydraulic	Hydraulic
Max cleaning discs:	10	7	5	10 or 2xFNC8	10 or 2xFNC8	7 or 1xFNC8	2	2	2	2
Recommended cage circumference:	Up to 200 meter	Up to 200 meter	Up to 120 meter	Up to 200 meter	Up to 200 meter	Up to 200 meter	Up to 90 meter	Up to 90 meter	Up to 90 meter	Up to 200 meter
Standard equipment:	Powder Coated or Stainless Steel Acoustic Cabinet, Integrated Centrifugal Suction Pump & High Pressure Pump.	Powder Coated or Stainless Steel Acoustic Cabinet, Integrated Centrifugal Suction Pump & High Pressure Pump.	Powder Coated or Stainless Steel Acoustic Cabinet, Integrated Centrifugal Suction Pump & High Pressure Pump.	Powder Coated Cabinet, 100m high pressure hose, boost pump 230-400V.	Integrated in an engine room. 100m high pressure hose, boost pump 230-400V, power nozzle.	Power Coated Cabinet, 100m high pressure hose, boost pump 230-400V.	40m high pressure hose, 3m suction hose, power nozzle with 40cm extension and swivel.	Stainless steel frame in Euro pallet size with lifting lugs.	Integrated pump	Integrated pump
Water, liter/min:	300	240	136	530	530	309	28	28	28	30
Bar:	240	280	280	240	240	225	280	280	280	200
 ● 300 cm	AKVA FNC8 Net Cleaner with remote control.	Recommended for FNC8.	Recommended for FNC8.	-	Recommended for 2 x FNC8.	Recommended for 2 x FNC8.	Recommended for FNC8.	-	-	-
 ● 270 cm*	7 disc washing rig in stainless steel.	Recommended for 7 disc rig.	Recommended for 7 disc rig.	-	Recommended for 7 disc rig.	Recommended for 7 disc rig.	Recommended for 7 disc rig.	-	-	-
 ● 180 cm	5 disc washing rig in stainless steel.	-	Recommended for 5 disc rig.	Recommended for 5 disc rig.	Recommended for 5 disc rig.	Recommended for 5 disc rig.	Recommended for 5 disc rig.	-	-	-
 ● 90 cm	2 disc washing rig in stainless steel.	-	-	-	-	-	Recommended for 2 discs.	Recommended for 2 discs.	Recommended for 2 discs.	Recommended for 2 discs.
 ● 30 cm (Shaft model)	Single washing rig in stainless steel.	-	-	-	-	-	Recommended for single disc.	Recommended for single disc.	Recommended for single disc.	Recommended for single disc.

* The traditional cleaner disks we use have a user range from 15 – 40 liter per minute (lpm) of water for each disc. The nozzle dimension (diameter) will give the recommended pressure, which shall not override 300 Bar.

** Alternative engine solutions. (For more details contact our sales offices).