

# SUB-fighter 3000 2.0

- ROV designed for tough conditions
- Reliable and well proven design
- Quick and easy mobilization
- Very good stability
- Plenty of power
- Interface for standard tools
- Quality at an affordable price
- Require a minimum of maintenance
- Made in Norway



<b>Vehicle</b>	LWH 110 x 67 x 61 cm
<b>Frame</b>	Aluminium
<b>Housings</b>	2 x electronic pressure bottles
<b>Weight in air</b>	145 kg. (approx.) basic standard vehicle
<b>Payload</b>	5-10 kg
<b>Working depth ROV</b>	350m
<b>Buoyancy</b>	Solid cell structure
<b>Power input</b>	230 VAC, 3 phase, 3 kW
<b>Thrusters</b>	4 thrusters 600 W pressure compensated, each 140 N
<b>Speed</b>	Horizontal 2.0 knot, Lateral 1 knot, Vertical 1.0 knot
<b>Camera</b>	HD IP camera. 1 standard - 2 optional
<b>Pan / Tilt</b>	Tilt angle: 90 degrees, Pan angle 45 degrees
<b>Lights</b>	Standard light 2 x Bowtech LED lamps. Dimmable
<b>Sensors</b>	30 bar depth sensor Sperre gyro compass Moist sensor
<b>Auto functions</b>	Auto depth, Auto heading
<b>Additional Equipment</b>	E1 manipulator with grabber and rope cutter
<b>Topside Power and Control</b>	Standard ROV/FNC topside power and control

DAT-083